

Bakker Magnetics Chute Magnets



For more information on this product, contact us on Tel: **01525 372714** Email: Sales@LHS.uk.com Web: <http://www.LHS.uk.com>

- Execution : Chute magnet type BKM
Sturdy construction
Permanent magnetic
Manual cleaning
Standard fitted with flat undrilled flanges
- Housing : Stainless steel 1.4301
- Surface treatment : Outside painted blue RAL5015
- Magnetic part : Permanent ceramic magnets quality BM7 or
Permanent Neodymium magnets quality BM35

Under normal circumstances Bakker Magnetics provides a life-time guarantee on the applied ceramic magnets. Bakker Magnetics supplies a complete installation and user manual in English.

Also available:

- Execution with manual cleaning tray.
- Execution with cleaning plates.
- Sanitary execution with EN 1092-1 flanges, for hygienic circumstances, blasted instead of painted High pressure version (BKM/HP).
- Special dimensions and/ or flanges (like Jacob flanges).

Standard ceramic version, no cleaning tray (BKM)

Article Number	A	B	C	D	Weight (kg)
26.210	100	400	183	167	27
26.211	150	480	233	261	57
26.212	200	570	283	371	115
26.213	250	690	333	464	205
26.214	300	695	383	514	260

Standard ceramic version, with cleaning tray (BKM/L)

Article Number	A	B	C	D	Weight (kg)
26.200	100	480	153	165	31
26.201	150	600	203	255	67
26.202	200	700	253	369	130
26.203	250	860	303	461	225
26.204	300	900	353	511	285

Standard ceramic version, with stainless steel cleaning plates (BKM/S)

Article Number	A (NW)	B	C	D	Weight (kg)
26.220	100	420	183	167	31
26.221	150	510	233	261	67
26.222	200	610	283	371	125
26.223	250	750	333	464	220
26.224	300	760	383	514	277

Sizes and dimensions in mm