



Bakker Magnetics Magbox Magnets



□ Execution	Magbox magnet MBM Sturdy construction Permanent magnetic Manual cleaning or semi-automatic cleaning Standard fitted with flat undrilled flanges
□ Housing	Steel S235 or Stainless steel 1.4301
□ Surface treatment	Outside painted blue RAL5015
□ Magnetic part	Permanent ceramic magnets quality BM7 or Permanent Neodymium magnets quality BM35

Under normal circumstances Bakker Magnetics provides a life-time guarantee on the applied ceramic magnets.

Bakker Magnetics supplies a complete installation and user manual in English.

Also available:

- Execution as semi-automatic version with EN 1092-1 flanges, for hygienic circumstances, blasted instead of painted (*MBM/A*).
- Execution with easy clean grids.

Special dimensions and/or flanges (like Jacob flanges).

Standard Ceramic Version (MBM)

Article Number	Height	Width	Depth	Weight (kg)
25.200	50	130	184	19
25.201	100	180	194	28
25.202	150	230	204	37
25.203	200	280	214	46
25.204	250	330	220	55
25.205	300	400	230	71

Semi-automatic Ceramic Version (MBM/A)

Article Number	Height	Width	Depth	Weight (kg)
25.220	50	165	281	9
25.221	100	220	282	11
25.222	150	285	294	12
25.223	200	340	297	14
25.224	250	395	299	17
25.225	300	445	322	20

Sizes and dimensions (in mm)

For more information on this product range, contact us on Tel: **01525 372714** Email: Sales@LHS.uk.com Web: <http://www.LHS.uk.com>